

Traffic Supervisor Exam
(ACTUAL 2025) Questions
And Correct VERIFIED
Answers

A flashing arrow panel used on high speed, high volume roadways must be what size?

- A. 60" x 30"
- B. 96" x 48"
- C. 48" x 24"
- D. 118" x 60" - <<<Answers>>>96" x 48"

What would the merging taper length be for a flagger taper be if the speed limit was 55 mph on a 12' wide lane?

- A. 700'
- B. 100'
- C. 660'
- D. 500' - <<<Answers>>>100'

If less than 90% of the pixels per character are operating in the PCMS, it is considered a marginal quality standard.

- A. True
- B. False - <<<Answers>>>False

What is the minimum merging taper length for one 12' lane closure on 55 MPH Multi-Lane Divided Highway?

- A. 660

B. 550

C. 1020

D. 700 - <<<Answers>>>660

Spalls greater than ____ on temporary barrier is considered unacceptable.

A. 0.5"

B. 1"

C. 1.5"

D. 6" - <<<Answers>>>1.5"

How many drums are needed in a 1,200 FT Tangent Section on a 65 MPH Highway?

A. 25

B. 10

C. 16

D. 40 - <<<Answers>>>10

While adjusting Sign spacing to avoid conflict with existing signs, _____ is the minimum spacing to existing signs for speeds of 45 MPH or less.

A. 100'

B. 200'

C. 300'

D. 400' - <<<Answers>>>200'

A minimum of ___ drums shall be used to close upstream shoulder.

A. 5

B. 8

C. 10

D. We don't need to close the shoulder while we are closing the lane. - <<<Answers>>>5

Shadow vehicle is optional for Mobile Operations on 2-Lane Road

A. True

B. False - <<<Answers>>>>false

128. The maximum width of Portable Barrier Wall opening between the impact attenuator and the outside edge of the paved shoulder shall be ____.

A. 5'

B. 10'

C. 9'

D. 12' - <<<Answers>>>9'

129. The sign spacing on Urban high-speed roadway should be ____.

A. 100'

B. 350'

C. 500'

D. 700' - <<<Answers>>>350'

Maximum distance between the Stop Bar and Traffic Signal Support location during Signalized Closing 1 Lane of a 2-Lane Highway is ____.

A. 50'

B. 75'

C. 100'

D. 150' - <<<Answers>>>75'

The spacing between work zone signs as shown in the SCDs are the minimums. Maximum spacing should not be greater than ____ times the distance as shown in SCDs.

A. 1.25

B. 1.5

C. 1.75

D. 2 - <<<Answers>>>1.5

What is the distance between "One Lane Road Ahead" sign and Flagger during Flagger closing 1 Lane of 2 - Lane 45 MPH Highway?

- A. 350'
- B. 500'
- C. 700'
- D. 1,000' - <<<Answers>>>350

While delineating traffic greater than 4' on 45 MPH multi-lane highway, the spacing of

RPMs within the transition areas is ____.

- A. 20'
- B. 10'
- C. 40'
- D. 30' - <<<Answers>>>20'

The snow-plowing season shall be from ____ through ____ unless otherwise specified in the plans.

- A. Oct 15th - Mar 15th
- B. Nov 15th - Mar 31st
- C. Oct 15th - Mar 31st
- D. Nov 1st - Apr 1st - <<<Answers>>>Oct 15th - Mar 31st